

HC 500 with protective grid

Item number: 250.34.3500.2

€ 2.482,86

EAN: 8413893038173

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like.

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like. Air volumes from approx. 1,000 m³/h to 9,000 m³/h.

The models can be supplied in 400 V. 230 V. Fan frame and motor housing made of lacquered aluminium. Propeller in fiberglass reinforced plastic. Thermal protection of motor. Vibration dampened engine mount. Closed engine, water and dustproof (Class B). Protection class IP 65. Internal protective grid. External blinds are supplied as an additional accessory. Temperature range - 40°C - + 70°C. Adjustment option Can be mounted either horizontally or vertically. Propeller blades with 34° angle. Protection class IP 65.



Specifications

Energy consumption [W]	675
Luftmængde ved 0 Pascal [m ³ /t]	9140
Kapslingsklasse	IP65
Minimum sound pressure at 3 meters [dB(A)]	68
Control	None
Material	Black painted steel

HC 400 with protective grid

Item number: 250.34.3400.2

€ 1.712,70

EAN: 8413893613189

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like.

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like. Air volumes from approx. 1,000 m³/h to 9,000 m³/h.

The models can be supplied in 400 V. 230 V. Fan frame and motor housing made of lacquered aluminium. Propeller in fiberglass reinforced plastic. Thermal protection of motor. Vibration dampened engine mount. Closed motor, water and dustproof (Class B). Protection class IP 65. Internal protective grid. External blinds are supplied as an additional accessory. Temperature range - 40°C - + 70°C. Adjustment option Can be mounted either horizontally or vertically. Propeller blades with 34° angle. Protection class IP 65.



Specifications

Energy consumption [W]	271
Luftmængde ved 0 Pascal [m ³ /t]	4920
Kapslingsklasse	IP65
Minimum sound pressure at 3 meters [dB(A)]	62
Control	None
Material	Black painted steel

HC 355 with protective grid

Item number: 250.34.3355.2

€ 1.817,54

EAN: 8413893612694

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like.

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like. Air volumes from approx. 1,000 m³/h to 9,000 m³/h.

The models can be supplied in 400 V. 230 V. Fan frame and motor housing made of lacquered aluminium. Propeller in fiberglass reinforced plastic. Thermal protection of motor. Vibration dampened engine mount. Closed engine, water and dustproof (Class B). Protection class IP 65. Internal protective grid. External blinds are supplied as an additional accessory. Temperature range - 40°C - + 70°C. Adjustment option Can be mounted either horizontally or vertically. Propeller blades with 34° angle. Protection class IP 65.



Specifications

Energy consumption [W]	168
Luftmængde ved 0 Pascal [m ³ /t]	3470
Kapslingsklasse	IP65
Minimum sound pressure at 3 meters [dB(A)]	59
Control	None
Material	Black painted steel

HC 315 with protective grid

Item number: 250.34.3315.2

€ 1.316,54

EAN: 8413893036780

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like.

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like. Air volumes from approx. 1,000 m³/h to 9,000 m³/h.

The models can be supplied in 400 V. 230 V. Fan frame and motor housing made of lacquered aluminium. Propeller in fiberglass reinforced plastic. Thermal protection of motor. Vibration dampened engine mount. Closed motor, water and dustproof (Class B). Protection class IP 65. Internal protective grid. External blinds are supplied as an additional accessory. Temperature range - 40°C - + 70°C. Adjustment option Can be mounted either horizontally or vertically. Propeller blades with 34° angle. Protection class IP 65.



Specifications

Energy consumption [W]	125
Luftmængde ved 0 Pascal [m ³ /t]	2220
Kapslingsklasse	IP65
Minimum sound pressure at 3 meters [dB(A)]	55
Control	None
Material	Black painted steel

HC 250 with protective grid

Item number: 250.34.3250.2

€ 1.245,96

EAN: 8413893081773

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like.

Propeller fans, which are especially intended for industrial purposes, such as extraction from warehouses, workshops and the like. Air volumes from approx. 1,000 m³/h to 9,000 m³/h.

The models can be supplied in 400 V. 230 V. Fan frame and motor housing made of lacquered aluminium. Propeller in fiberglass reinforced plastic. Thermal protection of motor. Vibration dampened engine mount. Closed engine, water and dustproof (Class B). Protection class IP 65. Internal protective grid. External blinds are supplied as an additional accessory. Temperature range - 40°C - + 70°C. Adjustment option Can be mounted either horizontally or vertically. Propeller blades with 34° angle. Protection class IP 65.



Specifications

Energy consumption [W]	77
Luftmængde ved 0 Pascal [m ³ /t]	1090
Kapslingsklasse	IP65
Minimum sound pressure at 3 meters [dB(A)]	49
Control	None
Material	Black painted steel

HC with protective grid

Item number:

€ 1.064,51

EAN: 8413893081773

Specifications

Energy consumption [W]

77

Control

None

